

EVEREST 3000

ISO 18752

RECOMMENDED FOR:
DEVELOPED TO WITHSTAND VERY DEMANDING CONDITIONS, VERY HIGH PERFORMANCE IN PRESSURE, PULSING AND FLEXING



RACCOMANDATO PER:
SVILUPPATO PER RESISTERE A CONDIZIONI MOLTO IMPEGNATIVE, PRESTAZIONI MOLTO ELEVATE IN PRESSIONE, IMPULSI E FLESSIONE

Features



Code	Hose size			Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	D.N.	Inch	mm	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Lb/ft	kg/mt
TSER320	31	1" 1/4	31,8	1,83	46,50	3000	210	12000	840	8,27	210	1,71	2,55
TSER324	38	1" 1/2	38	2,05	52,00	3000	210	12000	840	9,84	250	2,01	2,99

	Everest 3000 1"1/4"	(31,8mm)	ISO 18752 Flame Resistant MSHA IC-247	210 Bar 21,0 MPa	3000 Psi
---	----------------------------	----------	--	---------------------	-----------------

MARKING/MARCATURA: TRANSFER TAPE

OPERATING TEMPERATURE RANGE:

- 40°C/+120°C
(-40°F / +248°F)
with peaks of 125°C (257°F)

TUBE:

oil resistant synthetic rubber

REINFORCEMENT:

4 high tensile steel spirals

COVER:

special synthetic rubber

TEMPERATURA DI ESERCIZIO:

- 40°C/+120°C
(-40°F / +248°F)
con punte di 125°C (257°F)

SOTTOSTRATO:

gomma sintetica resistente agli oli

RINFORZO:

4 spirali di acciaio ad alto carico

COPERTURA:

gomma sintetica speciale

TYPE APPROVAL:

MSHA