

# EVEREST 4000

ISO 18752

## RECOMMENDED FOR:

DEVELOPED TO WITHSTAND VERY DEMANDING CONDITIONS, VERY HIGH PERFORMANCE IN PRESSURE, PULSING AND FLEXING

## RACCOMANDATO PER:

SVILUPPATO PER RESISTERE A CONDIZIONI MOLTO IMPEGNATIVE, PRESTAZIONI MOLTO ELEVATE IN PRESSIONE, IMPULSI E FLESSIONE



## Features



| Code    | Hose size |      |      | Outside diameter |       | Max working pressure |     | Min burst pressure |      | Min bend radius |     | Weight |       |
|---------|-----------|------|------|------------------|-------|----------------------|-----|--------------------|------|-----------------|-----|--------|-------|
|         | D.N.      | Inch | mm   | Inch             | mm    | PSI                  | Bar | PSI                | Bar  | Inch            | mm  | Lb/ft  | kg/mt |
| TSER406 | 10        | 3/8" | 9,5  | 0.78             | 19,90 | 4000                 | 280 | 16000              | 1120 | 2.56            | 65  | 0,38   | 0,57  |
| TSER408 | 12        | 1/2" | 12,8 | 0.90             | 23,00 | 4000                 | 280 | 16000              | 1120 | 3,54            | 90  | 0,52   | 0,77  |
| TSER410 | 16        | 5/8" | 16,0 | 1.06             | 27,00 | 4000                 | 280 | 16000              | 1120 | 3.94            | 100 | 0,63   | 0.97  |
| TSER412 | 19        | 3/4" | 19,0 | 1.18             | 30,10 | 4000                 | 280 | 16000              | 1120 | 4,72            | 120 | 0,87   | 1,30  |
| TSER416 | 25        | 1"   | 25,4 | 1,49             | 37,80 | 4000                 | 280 | 16000              | 1120 | 5,90            | 150 | 1,19   | 1,77  |
|         |           |      |      |                  |       |                      |     |                    |      |                 |     |        |       |
|         |           |      |      |                  |       |                      |     |                    |      |                 |     |        |       |
|         |           |      |      |                  |       |                      |     |                    |      |                 |     |        |       |
|         |           |      |      |                  |       |                      |     |                    |      |                 |     |        |       |


**Everest 4000 3/4"**

(19 mm)

 ISO 18752  
 Flame Resistant MSHA IC-247

 280 Bar  
 28,0 MPa

**4000 Psi**

MARKING/MARCATURA: TRANSFER TAPE

## OPERATING

## TEMPERATURE RANGE:

- 40°C/+120°C

(-40°F / +248°F)

with peaks of 125°C (257°F)

## TUBE:

oil resistant synthetic rubber

## REINFORCEMENT:

4 high tensile steel spirals

## COVER:

special synthetic rubber

## TEMPERATURA

## DI ESERCIZIO:

- 40°C/+120°C

(-40°F / +248°F)

con punte di 125°C (257°F)

## SOTTOSTRATO:

gomma sintetica resistente agli oli

## RINFORZO:

4 spirali di acciaio ad alto carico

## COPERTURA:

gomma sintetica speciale

## TYPE APPROVAL:

