

TEKNO R3

EN 854 R3 - SAE 100 R3 - ISO 4079 R3

RECOMMENDED FOR:
LOW AND MEDIUM PRESSURE, RETURN LINES

RACCOMANDATO PER:
LINEE DI BASSA E MEDIA PRESSIONE E LINEE DI RITORNO



Code	Hose size			Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	D.N.	Inch	mm	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Lb/ft	kg/mt
THR303	5	3/16"	4,8	0,500	12,70	1522	105	6091	420	2,953	75	0,10	0,16
THR304	6	1/4"	6,4	0,563	14,30	1261	87	5047	348	2,953	75	0,12	0,19
THR305	8	5/16"	7,9	0,688	17,50	1218	84	4873	336	3,934	100	0,18	0,27
THR306	10	3/8"	9,5	0,751	19,10	1131	78	4525	312	3,934	100	0,20	0,30
THR308	12	1/2"	12,8	0,936	23,80	1015	70	4061	280	4,917	125	0,29	0,44
THR310	16	5/8"	16,0	1,062	27,00	884	61	3538	244	5,507	140	0,34	0,50
THR312	19	3/4"	19,0	1,251	31,80	754	52	3016	208	5,901	150	0,47	0,70
THR316	25	1"	25,4	1,499	38,10	566	39	2262	156	8,065	205	0,58	0,87
THR320	31	1" 1/4	31,8	1,751	44,50	377	26	1508	104	9,843	250	0,67	1,00

**TEKNO R3****3/8"**

(9,5mm)

EN 854 3TE
SAE 100 R378 Bar
7,8 MPa**1131 Psi**

MARKING/MARCATURA: TRANSFER TAPE

OPERATING**TEMPERATURE RANGE:**

- 40°C/+100°C
(-40°F to +212°F)

TUBE:

oil resistant synthetic rubber

REINFORCEMENT:

2 high tensile textile braids

COVER:

weather resistant synthetic rubber.

TEMPERATURA**DI ESERCIZIO:**

- 40°C/+100°C
(-40°F to +212°F)

SOTTOSTRATO:

gomma sintetica resistente agli oli

RINFORZO:

2 trecce tessili ad alto carico

COPERTURA:

gomma sintetica resistente agli agenti atmosferici.