


INTERLOCK METRIC FEMALE 24° CONE - S TYPE



FEMMINA DIRITTA METRICA 24° DKOS CON O-RING
 FEMELLE DROIT MÉTRIQUE AVEC O-RING CÔNE 24° - SÉRIE S
 DKO-S INNENGEWINDE MIT O-RING 24° KONUS
 HEMBRA RECTA MÉTRICA CON O-RING CONO 24° - SERIE S

Code	Tube			Thread	Dimensions			Pressure	
	D.N.	Hose	Diam		T	D	H	A	Bar
	Inch		mm	mm	mm	mm	mm		
KFE1030S20	-10	5/8"	16	M30 x 2	20			420	6091
KFE1230S20	-12	3/4"	19	M30 x 2	20	36	35	420	6091
KFE1236S25	-12	3/4"	19	M36 x 2	25	46	36	420	6091
KFE1636S25	-16	1"	25.4	M36 x 2	25	46	37	414	6004
KFE1642S30	-16	1"	25.4	M42 x 2	30	50	38	280	4061
KFE2042S30	-20	1.1/4"	31.8	M42 x 2	30	50	40	250	3626
KFE2052S38	-20	1.1/4"	31.8	M52 x 2	38	60	45.5	250	3626
KFE2452S38	-24	1.1/2"	38.1	M52 x 2	38	60	45.5	250	3626